

1/4 Turn Dual Outlet Angle Stop Valve

Feature:

- ✓ Forged Lead Free Brass Body
- ✓ Chrome plated and rough brass
- ✓ Precision machined brass ball provides smooth operation and long lasting durability
- ✓ Two high performance O-rings provide high temperature and corrosion resistant.
- ✓ 100% leak tested
- ✓ Window box package



Working Pressure & Temperature:

- 125 psi Maximum
- Temperature 40°F to 180°F


Approvals:

IAPMO NSF/ANSI-61 NSF/ANSI-372
ASME A112.18.1



Part Name	Material
1 Body	Lead Free Brass
2 Adapter	Lead Free Brass
3 Ball	Lead Free Brass
4 Seal	PTFE
5 Stem	LF Brass Alloy
6 O-ring	NBR
7 Handle	ABS
8 Screw	Stainless Steel
9 O-ring	NBR
10 Sleeve	Lead Free Brass
11 Nut	Brass
12 Sleeve	Lead Free Brass
13 Nut	Brass

Part #	Description
4A3838	1/2 Nom. Compression x 3/8" OD Compression x 3/8" OD Compression
4A3814	1/2 Nom. Compression x 3/8" OD Compression x 1/4" OD Compression



Dimensions		
Model	H	W
4A3838	2.39	2.14
4A3814	2.39	2.04

*Unit in inch

